

SAFETY DATA SHEET

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

1. Identification

Product identifier	Potassium Hydroxide Solution	
Other means of identification	Caustic Potash Solution, KOH, Potash Lye, Lye, Lye Solution	
Product family	Alkali Metal Hydroxide	
Recommended use	Saponification of fats; manufacture of biodiesel, soft soaps, fine chemicals, fertilizers, electrolyte for batteries	
Recommended restrictions	None known	
Manufacturer/Importer/Supplier/Distributor information		
Manufacturer		
Company name	ERCO Worldwide	
Address	302 The East Mall Suite 200 Toronto, ON M9B 6C7 Canada	
Telephone	(416) 239-7111 (M- F: 8:00 am – 5:00pm EST)	
Website	http://www.ercoworldwide.com	
E-mail	productinfo@ercoworldwide.com	
Emergency phone number	Canada: 613-996-6666 (CANUTEC) USA: 1-800-424-9300 (CHEMTREC)	
Supplier	Refer to Manufacturer	

2. Hazard(s) Identification

Physical hazards	Corrosive to metals	Category 1
Health hazards	Acute toxicity, oral	Category 3
	Skin corrosion	Category 1A
	Serious eye damage	Category 1
	Specific target organ toxicity, single exposure	Category 3 respiratory tract irritation
Environmental hazards	Not currently regulated by OSHA, refer to Section 12 for additional information.	
OSHA defined hazards	This mixture does not meet the classification criteria according to OSHA HazCom 2012.	

Label elements



Signal word	Danger
Hazard statement	May be corrosive to metals. Toxic if swallowed. Causes severe skin burns and eye damage. Causes serious eye damage. May cause respiratory irritation.
Precautionary statement	
Prevention	Keep only in original container. Wash hands and face thoroughly after handling. Do not eat, drink or smoke when using this product. Do not breathe dusts or mists. Wear protective gloves, protective clothing, eye protection, face protection. Use only outdoors or in a well-ventilated area
Response	Immediately call a POISON CENTER or doctor/physician. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse. IF INHALED: Remove person to fresh air and keep comfortable for breathing. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Absorb spillage to prevent material damage.
Storage	Store in a corrosion resistant container with a resistant inner liner. Store in a well-ventilated place. Keep container tightly closed. Store locked up.
Disposal	Dispose of contents and container in accordance with local/regional/national/international regulations.
Hazard(s) not otherwise classified (HNOC)	No OSHA defined hazard classes. Other hazards which do not result in classification: Contact with most metals will generate flammable hydrogen gas. Contact with water will generate considerable heat. Reacts vigorously or violently with many organic and inorganic chemicals such as: acids, acrolein, acrylonitrile, chlorinated hydrocarbons (e.g. 1,2 dichloroethylene), chlorine dioxide, maleic anhydride, nitroethane, nitroparaffins, 2-nitrophenol, nitropropane, phosphorus, potassium persulfate, and tetrahydrofuran (containing peroxides). Chronic skin contact with low concentrations may cause dermatitis.
Supplemental information	Not applicable.

3. Composition/Information on Ingredients

Chemical name	Common name and synonyms	CAS number	Conc. % By Weight
Potassium Hydroxide	Caustic Potash, Lye, Potash, Potash Lye	1310-58-3	50 or less w/w%
Dihydrogen oxide	Water	7732-18-5	Balance
Chemical name of impurities, stabilizing solvents and/or additives:			None

4. First-Aid Measures

Inhalation	Move to fresh air. If breathing is difficult, give oxygen. If breathing stops, give artificial respiration. Induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device. Immediately call a POISON CENTER or doctor/physician if symptoms develop or persist.
Skin Contact	Take off immediately all contaminated clothing. Immediately flush skin with running water for at least 20 minutes. Cover wound with sterile dressing. Do not rub area of contact. Wash contaminated clothing before reuse. Leather and shoes that have been contaminated with the solution may need to be destroyed. Immediately call a POISON CENTER or doctor/physician.
Eye Contact	Immediately flush eyes, by holding the eyelids apart, with plenty of water for at least 20 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Take care not to rinse contaminated water into the unaffected eye or onto the face. Immediately call a POISON CENTER or doctor/physician.
Ingestion	Rinse mouth. Do NOT induce vomiting. Never give anything by mouth to a victim who is unconscious or is having convulsions. Have a conscious person drink a glass of water or milk immediately if able to swallow. Immediately call a POISON CENTER or doctor/physician.
Most important symptoms/effects, acute and delayed	<p>Inhalation of mists can cause severe respiratory irritation. Symptoms may include coughing, choking and wheezing. Inhalation could result in pulmonary edema (fluid accumulation). Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.</p> <p>Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring. Corrosive to the eyes and may cause severe damage including blindness. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. May be harmful or fatal if swallowed. May cause severe irritation and corrosive damage in the mouth, throat and stomach. Symptoms may include abdominal pain, vomiting, burns, perforations, bleeding and eventually death.</p>

Indication of immediate medical attention and special treatment needed Immediate medical attention is required. Causes chemical burns. Toxic if swallowed. Symptoms may be delayed. Probable mucosal damage may contraindicate the use of gastric lavage.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Show this safety data sheet to the doctor in attendance.

5. Fire-Fighting Measures

Suitable extinguishing media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Use as appropriate: Water Spray or Fog. Alcohol resistant foam. Dry chemical powder. Use water with caution. Contact with water will generate considerable heat and cause spattering if applied directly to potassium hydroxide.

Unsuitable extinguishing media Carbon dioxide (CO₂).
Use chemical extinguishing agents with caution. Some chemical extinguishing agents may react with this material.

Specific hazards arising from the chemical Not considered flammable. Contact with most metals will generate flammable hydrogen gas. Contact with water will generate considerable heat. The heat that is generated may be sufficient enough to ignite nearby combustible materials. Reacts vigorously or violently with many organic and inorganic chemicals such as: acids, acrolein, acrylonitrile, chlorinated hydrocarbons (e.g. 1,2 dichloroethylene), chlorine dioxide, maleic anhydride, nitroethane, nitroparaffins, 2-nitrophenol, nitropropane, phosphorus, potassium persulfate, and tetrahydrofuran (containing peroxides). Toxic fumes, gases or vapours may evolve on burning.

Special protective equipment and precautions for firefighters Potassium hydroxide solid and solutions are very corrosive and at high temperatures decomposition occurs giving off strong, corrosive fumes of potassium oxide. Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. Chemical protective clothing (e.g. chemical splash suit) and positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Firefighting equipment/instructions Fight fire with normal precautions from a reasonable distance. Evacuate the area promptly. Move containers from fire area if you can do so without risk. Use water spray to cool unopened containers. Do not allow run-off from firefighting to enter drains or water courses. Dike for water control. Water must be used with extreme caution to extinguish a fire in an area where potassium hydroxide is stored and must not come into contact with the potassium hydroxide. Potassium hydroxide does not burn and does not

support combustion. However, closed containers may rupture violently when exposed to the heat of the fire. If possible, isolate materials not yet involved in the fire and move containers from the fire area if this can be done without risk and they have not been exposed to heat. If it is not possible to move containers, apply water in flooding quantities from the side and from a safe distance, to keep fire-exposed containers, tanks or car/trailer loads cool and absorb heat to help prevent rupture, and protect personnel. If necessary, use unmanned monitors and hose holders to keep cooling streams of water on fire-exposed tanks or containers until well after the fire is out. Water spray may also be used to knock down corrosive and toxic fumes and vapours which may be produced in a fire. Fire control or dilution water may be corrosive and/or toxic. Dike fire control water for appropriate disposal. Withdraw immediately in case of rising sound from venting safety device or any discoloration of tank. ALWAYS stay away from the ends of tanks, but be aware that flying material (shrapnel) from ruptured tanks may travel in any direction. Tanks or drums should not be approached directly after they have been involved in a fire, until they have been completely cooled down.

Specific methods	Use standard firefighting procedures and consider the hazards of other involved materials.
General fire hazards	Not available.
Hazardous combustion products	None known. In the event of fire the following can be released: Potassium oxides.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures	Immediately evacuate personnel to safe areas. Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ventilate closed spaces before entering them. For personal protection, see section 8 of the SDS.
--	---

Methods and materials for containment and cleaning up	Ventilate the area. Remove sources of ignition. Stop leak if you can do so without risk. Absorb spillage to prevent material damage. Use a non-combustible material like vermiculite, sand or earth to soak up the product and place into a container for later disposal. Use water spray to reduce vapors or divert vapor cloud drift.
--	---

Small Spills: Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand). Dilute alkali with water and neutralize with acids (e.g. acetic acid / vinegar).

Large Spills: Prevent entry into waterways, sewer, basements or confined areas. If not recoverable, dilute with water or flush to holding area and

neutralize. Remove with vacuum trucks or pump to storage/salvage vessels. Contact the proper local authorities.

Never return spills to original containers for re-use. Contaminated absorbent material may pose the same hazards as the spilled product. For waste disposal, see Section 13 of the SDS.

Environmental precautions

Avoid discharge into drains, water courses or onto the ground. Contact local authorities in case of spillage to drain/aquatic environment.

7. Handling and Storage

Precautions for safe handling

Wear chemically resistant protective equipment during handling. Wear protective gloves/clothing and eye/face protection. Do not breathe mist. Do not taste or swallow. Avoid contact with eyes, skin and clothing. Keep away from heat. Keep away from metals and other incompatibles. Label containers appropriately. Wash thoroughly after handling. When using, do not eat, drink or smoke. Avoid release to the environment. Any protective clothing or shoes which become contaminated with caustic potash should be removed immediately and thoroughly laundered before any reuse.

When diluting with water, slowly add caustic potash solution to cold water with mixing. Use cold water to prevent excessive heat generation. Heat will be produced during dilution. Never add water to the product. Full protective clothing, goggles and face shield should be worn. Do not add large quantities of water to caustic potash because excessive heat formation will cause boiling and spattering.

Conditions for safe storage, including any incompatibilities

Store in a cool, dry place out of direct sunlight. Store in a well-ventilated place. Store locked up. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Store away from incompatible materials (see Section 10 of the SDS). Store in original tightly closed container. Suitable container and packaging materials for safe storage: Polyvinyl chloride (PVC). Polypropylene. Polytetrafluoroethylene (PTFE). Mild steel may be used if the storage temperature does not exceed 50°C (122°F). For temperatures above 50°C (122°F), materials such as nickel or lined steel may be required.

Contact of caustic potash cleaning solutions with food and beverage products (in enclosed vessels or spaces) can produce lethal concentrations of carbon monoxide gas. Do not enter confined spaces such as tanks or pits without following proper entry procedures.

Aluminum equipment should not be used for storage and/or transfer.

8. Exposure Controls/Personal Protection

Occupational exposure limits

US. ACGIH Threshold Limit Values

Components	Type	Value
Potassium Hydroxide (CAS 1310-58-3)	Ceiling	2 mg/m ³

US. NIOSH: Pocket Guide to Chemical Hazards

Components	Type	Value
Potassium Hydroxide (CAS 1310-58-3)	TWA	2 mg/m ³

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Ensure adequate ventilation, especially in confined areas.

Individual protection measures, such as personal protective equipment

Safety shower and eyewash station must be provided in the immediate work area.

Eye/face protection

Wear eye/face protection. Chemical goggles and face shield are recommended. A full face respirator, in place of goggles and a face shield, will also provide excellent face protection.

Skin protection

Hand protection

Wear appropriate chemical resistant gloves. Wear as appropriate: Butyl rubber. Neoprene. Nitrile, Polyvinyl chloride (PVC), Viton™ rubber (fluor rubber). Advice should be sought from glove suppliers.

Other

Where contact is likely, wear chemical-resistant gloves, a chemical suit, rubber boots, and chemical safety goggles plus a face shield.

Respiratory protection

In case of insufficient ventilation, wear suitable respiratory equipment. A NIOSH/MSHA approved air-purifying respirator with the appropriate chemical cartridges or a positive-pressure, air-supplied respirator may be used to reduce exposure. Use a positive-pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air-purifying respirators may not provide adequate protection. Respirators should be selected based on the form and concentration of contaminants in air. Advice should be sought from respiratory protection specialists.

Thermal Hazards

Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations Do not breathe mist. Avoid contact with eyes, skin and clothing. When using, do not eat, drink or smoke. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove soiled clothing and wash it thoroughly before reuse. Handle in accordance with good industrial hygiene and safety practice.

9. Physical and Chemical Properties

Appearance	Clear to white/light gray, viscous liquid
Physical state	Liquid
Form	Viscous liquid
Color	Clear to white/light gray
Odor	Odorless
Odor threshold	Not Available
pH	> 14 (at high alkali concentration in water pH scale is not applicable)
Melting point/	39.2 °F (4 °C) (50% solution)
Freezing point	-22 °F (-30 °C) (45% solution)
Initial boiling point and boiling range	269.6 °F (132 °C) (45% solution) 289.4 °F (143 °C) (50% solution)
Flash point	Not Applicable (does not burn)
Evaporation rate	Not Available
Flammability (solid, gas)	Not Applicable
Upper/lower flammability or explosive limits	
Flammability limit – lower (%)	Not Applicable
Flammability limit – upper (%)	Not Applicable
Explosive limit – lower (%)	Not Available
Explosive limit – upper (%)	Not Available
Vapor pressure	27 mm Hg @ 60°C / 140°F (50% solution) 39 mm Hg @ 60°C / 140°F (45% solution)
Vapor density	Not available
Relative density	1.457 g/cm ³ @ 15.6°C / 60°F (45% solution) 1.516 g/cm ³ @ 15.6°C / 60°F (50% solution)
Solubility (ies)	
Solubility (water)	Soluble in all proportions
Solubility (other)	Soluble in ethanol, methanol and glycerol. Insoluble in diethyl ether and ammonia.
Partition coefficient (n-octanol/water)	Not Available
Auto-ignition temperature	Not Applicable
Decomposition temperature	Not Available
Viscosity	5.25 cSt @ 68°F / 20°C (50% solution)
Other information	
Specific gravity	1.46 @ 15.6°C / 60°F (45% solution) 1.52 @ 15.6°C / 60°F (50% solution)

10. Stability and Reactivity

Reactivity	Contact with most metals will generate flammable hydrogen gas. Contact with water will generate considerable heat. May be corrosive to metals. May be corrosive to: Aluminum. Bronze. Brass. Zinc.
Chemical stability	Material is stable under normal conditions. Rapidly absorbs moisture and carbon dioxide from the air forming potassium carbonate.
Possibility of hazardous reactions	Reacts vigorously or violently with many organic and inorganic chemicals such as: acids, acrolein, acrylonitrile, chlorinated hydrocarbons (e.g. 1,2 dichloroethylene, trichloroethylene), chlorine dioxide, maleic anhydride, nitroethane, nitroparaffins, 2-nitrophenol, nitropropane, phosphorus, potassium persulfate, and tetrahydrofuran (containing peroxides). Attacks plastics, such as polyethylene terephthalate, polybutylene terephthalate, thermoset polyesters (bisphenol-A fumarate (50-100%), isophthalic acid and general purpose), polyamide-imide (Torlon), polyurethane (rigid) and thermoset chlorinated polyester; elastomers, such as styrene-butadiene (SBR), polyacrylate, polyurethane, fluorosilicone, silicone, chlorinated polyethylene and soft rubber; and coatings, such as polyester and vinyls (5-100%) and epoxy (general purpose and chemical resistant epoxy) (50-100%) at room temperature.
Conditions to Avoid	Contact with incompatible materials. Avoid high temperatures. Do not use in areas without adequate ventilation
Incompatible materials	Metals. Water, moisture. Acrolein. Acrylonitrile. Chlorinated hydrocarbons. Chlorine dioxide. Maleic anhydride. Nitroethane. Nitroparaffins. Nitropropane. 2-nitrophenol. Phosphorus. Potassium persulfate. Tetrahydrofuran.
Hazardous decomposition products	None known. In the event of fire the following can be released: Potassium oxides.

11. Toxicological Information

Information on likely routes of exposure

Inhalation	May cause severe irritation to the nose, throat, and respiratory tract. Breathing of mist is possible. Breathing this material is harmful and can cause death.
Skin contact	Contact with the skin can cause severe burns with deep ulcerations. Contact with solution or mist can cause multiple burns with temporary loss of hair at burn site. Solutions may not cause immediate pain or irritation upon skin contact. Prolonged or repeated contact with dilute solutions may cause drying and cracking of skin and possible skin damage.

Eye contact	Causes burns, serious eye damage and permanent injury to eye tissue. Can cause blindness. Mist or dust can cause irritation with high concentrations causing destructive burns.
Ingestion	Swallowing this material may be harmful or cause death. Harmful effects include burns and permanent damage to the digestive tract, including the mouth, throat, stomach and intestines. Symptoms may include severe abdominal pain and vomiting of blood. Blood loss through damaged tissue can lead to low blood pressure and shock. Death can result from ingestion. There is one reported case of biaural hearing loss after accidental ingestion of potassium hydroxide.
Symptoms related to the physical, chemical and toxicological characteristics	<p>Inhalation of mists can cause severe respiratory irritation. Symptoms may include coughing, choking and wheezing. Symptoms of pulmonary edema (chest pain, shortness of breath) may be delayed.</p> <p>May cause severe irritation and corrosive damage in the mouth, throat and stomach. Symptoms may include abdominal pain, vomiting, burns, perforations, bleeding and eventually death. Direct skin contact may cause corrosive skin burns, deep ulcerations and possibly permanent scarring. Corrosive to the eyes and may cause severe damage including blindness. Symptoms may include stinging, tearing, redness, swelling, and blurred vision.</p>
Delayed and immediate effects and chronic effects from short-term and long-term exposure	
Effects of short-term (acute) exposure	Depending upon level and duration of exposure, other possible signs and symptoms from breathing, swallowing, and contact of this material with the skin may include: irritation of the nose, throat, airways, and lungs with cough, sneezing, perforation of the nasal septum, and blindness. Preexisting disorders of the following organs or systems which may be aggravated by exposure to this material (or a component) include: respiratory system (including asthma and other breathing disorders), and eyes.
Effects of long-term (chronic) exposure	This material may cause the following effects: eye damage, blindness, respiratory tract damage (nose, throat, airways) lung damage, skin damage, and gastrointestinal tract damage.
Information on toxicological effects	
Acute toxicity	Toxic if swallowed. The below product data is the calculated ATE values for this mixture. Individual ingredient component data appears below the product mixture ATE values.

Product	Species	Test Results
Potassium Hydroxide Solution (CAS Mixture)		
Acute		
<i>Dermal</i>		
LD ₅₀	Rabbit	> 2520 mg/kg
<i>Oral</i>		
LD ₅₀	Rat	410 mg/kg
Components	Species	Test Results
Potassium Hydroxide (CAS 1310 58-3)		
Acute		
<i>Dermal</i>		
LD ₅₀	Rabbit	> 1260 mg/kg
<i>Inhalation</i>		
LC ₅₀		No Data in Literature
<i>Oral</i>		
LD ₅₀	Rat	205 mg/kg
Water (CAS 7732-18-5)		
Acute		
<i>Dermal</i>		
LD ₅₀	Rabbit	Not available.
<i>Inhalation</i>		
LC ₅₀	Rat	Not available.
<i>Oral</i>		
LD ₅₀	Rat	> 89840 mg/kg
Skin corrosion	Hazardous by OSHA criteria. Category 1A. Causes severe skin burns and eye damage.	
Serious eye damage	Hazardous by OSHA criteria. Category 1. Causes serious eye damage.	
Respiratory or skin sensitization		
Respiratory sensitization	Not expected to be a respiratory sensitizer.	
Skin sensitizer	This product is not expected to be a skin sensitizer.	
Germ cell mutagenicity	Not expected to be mutagenic in humans.	
Carcinogenicity	This product is not considered to be a carcinogen by IARC, ACGIH, NTP, or OSHA.	
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.	

Reproductive toxicity	This product is not expected to cause reproductive or developmental effects.
Specific target organ toxicity - single exposure	Hazardous by OSHA criteria. Category 3. May cause respiratory irritation.
Specific target organ toxicity - repeated exposure	Not classified as a specific target organ toxicity -repeated exposure.
Aspiration toxicity	This product is not classified as an aspiration hazard.
Chronic effects	Chronic skin contact with low concentrations may cause dermatitis act.

12. Ecological Information

Ecotoxicity	Because of the high pH of this product, it would be expected to produce significant ecotoxicity upon exposure to aquatic organisms and aquatic systems. However, may be neutralized by naturally occurring acidity in the environment. The ingredient ecotoxicity data appearing below is expected to be primarily associated with ph.
--------------------	--

Components	Species	Test Results
Potassium Hydroxide (CAS 1310-58-3)		
Aquatic		
<i>Acute</i>		
Crustacea	EC ₅₀ Water flea (<i>Ceriodaphnia dubia</i>)	56 mg/l, 48 hours
Fish	LC ₅₀ Western mosquitofish (<i>Gambusia affinis</i>)	80 mg/l, 96 hours
Persistence and degradability	No data is available on the degradability of this product. Biodegradation is not applicable to inorganic substances. Potassium hydroxide will be neutralized by acidity present in natural environment.	
Bioaccumulative potential	No accumulation in living organisms is expected due to high solubility and dissociation properties.	
Mobility in soil	High water solubility indicates a high mobility in soil.	
Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

13. Disposal Considerations

Disposal instructions	Collect and reclaim or dispose in sealed containers at licensed waste disposal site. This material and its container must be disposed of as hazardous waste. Do not allow this material to drain into sewers/water
------------------------------	--

supplies. Do not contaminate ponds, waterways or ditches with chemical or used container. Dispose of contents and containers in accordance with local/regional/national/international regulations.

Local disposal regulations

Dispose in accordance with all applicable regulations.

Hazardous waste code

The waste code should be assigned in discussion between the user, the producer and the waste disposal company.

Waste from residues / unused products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).

Contaminated packaging

Empty containers should be taken to an approved waste handling site for recycling or disposal.

Since emptied containers may retain product residue, follow label warnings even after container is emptied.

14. Transport Information

DOT

UN number	UN1814
UN proper shipping name	Potassium hydroxide solution
Transport hazard class(es)	
Class	8
Subsidiary risk	None
Packing group	II
Special precautions for user	Read safety instructions, SDS and emergency procedures before handling. US CERCLA Reportable Quantity (RQ): 1000 lbs / 454 kg
Special provisions	B2; IB2; T7; TP2
Packaging exceptions	154
Packaging non bulk	202
Packaging bulk	242

IATA

UN number	UN1814
UN proper shipping name	Potassium hydroxide solution
Transport hazard class(es)	
Class	8
Subsidiary risk	None
Packing group	II
Environmental hazards	No
ERG Code	8L

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

Other information

 Passenger and cargo aircraft
 Cargo aircraft only

 Allowed
 Allowed

IMDG
UN number

UN1814

UN proper shipping name

Potassium hydroxide solution

Transport hazard class(es)
Class

8

Subsidiary risk

None

Packing group

II

Environmental hazards
Marine pollutant

No.

EmS

F-A, S-B

Special precautions for user

Read safety instructions, SDS and emergency procedures before handling.

 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code
 DOT

Not available.


IATA; IMBG


15. Regulatory Information

US federal regulations

This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication Standard, 29 CFR 1910.1200. All components are on the U.S. EPA TSCA Inventory List.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)	Not regulated.
CERCLA Hazardous Substance List (40 CFR 302.4)	Potassium hydroxide (CAS 1310-58-3) Listed.
SARA 304 Emergency release notification	Not regulated.
OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)	Not listed.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories	Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - Yes
SARA 302 Extremely hazardous substance	Not listed.
SARA 311/312 Hazardous chemical	No
SARA 313 (TRI reporting)	Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List	Not regulated.
Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)	Not regulated.
Safe Drinking Water Act (SDWA)	Not regulated.

US state regulations

US. Massachusetts RTK - Substance List	Potassium hydroxide (CAS 1310-58-3)
US. New Jersey Worker and	Not regulated.

Community Right-to-Know Act
US. Pennsylvania RTK – Hazardous Substances Potassium hydroxide (CAS 1310-58-3)

US. Rhode Island RTK

Potassium hydroxide (CAS 1310-58-3)

US. California Proposition 65

California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	Yes
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	Yes
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes
United States & Puerto Rico	Toxic Substances Control Act (TSCA) Inventory	Yes

*A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s).

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

16. Other Information

Issue date	3/28/2018
Revision #	2
Revision Indicator	Minor revisions to text and new layout of Safety Data Sheet.
List of abbreviations	ACGIH: American Conference of Governmental Industrial Hygienists CAS: Chemical Abstract Services CERCLA: Comprehensive Environmental Response, Compensation and Liability Act of 1980 CFR: Code of Federal Regulations DOT: Department of Transportation DSL: Domestic Substance List

EINECS: European Inventory of Existing Commercial chemical Substances
EPA: Environmental Protection Agency
EPCRA: Emergency Planning and Community Right-to-Know Act
HSDB® - Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
IATA: International Air Transport Association
IBC: Intermediate Bulk Container
ICAO: International Civil Aviation Organization
IMDG: International Maritime Dangerous Goods LC: Lethal Concentration
LD: Lethal Dose
NIOSH: National Institute of Occupational Safety and Health
NOEC: No observable effect concentration
NTP: National Toxicology Program
OECD: Organization for Economic Cooperation and Development
OSHA: Occupational Safety and Health Administration
PPE: Personal Protective Equipment
RCRA: Registry of Toxic Effects of Chemical Substances
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
SDS: Safety Data Sheet
STEL: Short Term Exposure Limit
TLV: Threshold Limit Values
TWA: Time Weighted Average

References

ACGIH Documentation of the Threshold Limit Values and Biological Exposure Indices (2014) Canadian Centre for Occupational Health and Safety, CCIInfoWeb Databases, 2014 (Chempendium, RTECs, HSDB, INCHEM)
Material Safety Data Sheet from manufacturer.
OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2014.

Disclaimer

Information presented in this SDS is furnished in accordance with OSHA's Hazard Communication Standard (HCS) 2012.

This information provided was developed and is provided for educational purposes and is not intended to be, nor should it be construed as, legal advice or as ensuring compliance with any laws or regulations of any jurisdiction. ERCO Worldwide, A division of Superior Plus LP ("ERCO") assumes no responsibility and shall have no liability for any inaccuracies, errors or omissions in, nor for any damages (including consequential, or indirect damages), losses, costs, fees, resulting from the use of, or reliance on, any part of this information. Likewise, ERCO assumes no responsibility for injury to, or the death of, recipient(s) or users of this information, or for any loss or damage to any property, arising from the use or consideration of this information. The recipient(s) and users, and each of their respective employees and agents, assume all responsibility and liability for all such risks, costs, losses, damages, fees, or otherwise, even if caused by the negligence, omission, default, or error in judgement of ERCO, its agents, subsidiaries, affiliates, or representatives.

Recipients or users of this information should ensure, and are responsible for, its compliance with the current state of the law and legislation applicable thereto, and the content of the laws and regulations of any other jurisdictions, as applicable. Any person receiving or using this SDS is responsible for and must exercise their own judgment and due diligence in ensuring safe and lawful use and handling of any product or information, as they assume the risk of suing or relying on any information contained herein.