



SALES SPECIFICATION

Liquid Caustic Potash

(KOH, Potassium Hydroxide)

Port Edwards Plant

MEMBRANE TECHNICAL GRADE

<u>COMPONENT</u>	<u>LIMIT</u>
Total Alkalinity, as KOH, % (weight):	
45% solution	45 – 47
50% solution	50 – 52
Chloride, as KCl, % (weight)	0.0050 max.
Iron, as Fe, ppm (weight)	2.0 max.
Sodium, as Na, ppm (weight)	1500 max.
Nickel, as Ni, ppm (weight)	0.30 max.

Meets [current](#) test requirements of **ANSI/AWWA Standard B511**.

NSF listed as complying with **NSF/ANSI/CAN Standard 60**.

Meets the test requirements of **MIL-DTL-11751F, class 2** (only 45%).

Meets [current](#) **Food Chemical Codex** specifications.

Star-K Kosher certified

IFANCA® Halal certified

The information presented is not guaranteed although it was prepared by ERCO's technical personnel and is intended to be accurate to the best of our knowledge. No warranties or guarantees, expressed or implied, are made regarding performance, stability, or otherwise. This information is not intended to be all-inclusive as the conditions of use, handling, storage, and other factors may involve additional safety or performance considerations.